

Technical Data Sheet



Eclectic Products, Inc.
Manufacturing Facility
101 Dixie Mae Drive
Pineville, Louisiana
eclecticproducts.com
800.349.4667

ISO 9001:2008
Compliant
Quality Management
Systems

Administration Office
Eugene, Oregon
eclecticproducts.com
800.693.4667



Gallon | Quart | Pint

WOOD-TEX[®] SYNTHETIC WOOD FILLER

PRODUCT DESCRIPTION

Wood-Tex[®] is a resin-based wood filler, developed for the plywood and furniture industries, used to repair defects in plywood, furniture, laminated beams, cabinet work, and other woodworking applications. It molds like putty and is consistent, uniform, waterproof and fast-setting with minimal shrinkage. Made with genuine wood flour, Wood-Tex[®] can be sanded, stained, sawed, planed or drilled like ordinary wood.

WHERE TO USE / APPLICATIONS

Use to fill cracks or holes in wood. Spread evenly into cracks or hole, let dry and sand smooth to surface repaired. Paint or stain to match wood surface.

FEATURES AND BENEFITS

ACTS LIKE REAL WOOD – saw, drill, sand, plane and nail

INTERIOR/EXTERIOR – use indoors or outdoors

WON'T CRACK OR SHRINK – spread evenly into cracks and holes without crumbling or cracking

SUPERIOR STRENGTH – hard finish with little or no shrinkage

QUALITY FINISH – takes stains and paints evenly with minimal sanding

TECHNICAL INFORMATION

PHYSICAL PROPERTIES

Colors (6):	Cherry/Dark Mahogany, Fir/Maple, Natural/Ash, Red Oak, Walnut, White Pine
VOC:	215 gram/liter
Solvent:	Acetone and Methyl Ethyl Ketone
Density:	12 to 13 lbs/gal
Solids:	75% +/- 1.0% (by weight)
Vehicle:	Nitrocellulose Lacquer
Storage:	Store between 45 and 85 °F (7 and 29 °C)
Freeze/thaw stability:	None; do not freeze
Shelf life:	1 year

DIRECTIONS and APPLICATION NOTES

Read all directions before using and test a small area before full use.

- Step 1 For best adhesion, cracks or defects should be clean and dry.
- Step 2 Press wood filler firmly into defect by hand, or with putty knife.
- Step 3 Lower temperatures require longer drying periods.
- Step 4 When dry, sand flush with surrounding surfaces.
- Step 5 Surfaces may be painted, varnished, lacquered, waxed or shellacked when wood filler is dry.
- Step 6 Close container after each use.

For technical assistance, call 800.767.4667.

Wood-Tex[®] Synthetic Wood Filler can be drilled, nailed, planed, or sawed like ordinary wood. Use FAMOWOOD[®] WOOD FILLER THINNER to restore wood filler to its original consistency.

HEALTH and SAFETY

Before working with this product, read and become familiar with information concerning hazards, proper use and handling. MSDS is available on line at:

eclecticproducts.com/msds/woodtex_english.pdf; to request an MSDS, please send an e-mail to msds@eclecticproducts.com or call 800.333.9826.

LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products, Inc., P.O. Box 4450, Pineville LA 71361 or call 800.767.4667. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.